



PLENUM

General use in air plenums without conduit for:

- Solid or stranded bare copper
 - Color coded low smoke flame retardant polymer alloy insulation
 - Natural low smoke flame retardant polymer alloy jacket
 - NEC article 725 or 800
 - UL listed CMP
 - Security systems
 - Sound and audio
 - Data, control and instrumentation
- 14 & 12 AWG CL2P or CL3P



CSC #	NO. OF COND	AWG	STRAND	NOM. INS THK	NOM. JKT THK	NOM. O.D.	PKG WT LBS/1000'
130775	4	22	SOLID	.009"	.015"	.132"	17
110105	2	22	7/30	.010"	.015"	.123"	13
110120	3	22	7/30	.010"	.015"	.132"	16
110205	4	22	7/30	.010"	.015"	.145"	17
110225	5	22	7/30	.010"	.015"	.161"	21
110250	6	22	7/30	.010"	.015"	.175"	26
110270	8	22	7/30	.010"	.015"	.180"	30
110400	10	22	7/30	.010"	.015"	.220"	39
110800	12	22	7/30	.010"	.015"	.227"	42
110820	15	22	7/30	.010"	.015"	.240"	55
110834	20	22	7/30	.010"	.015"	.284"	77
110838	25	22	7/30	.010"	.015"	.322"	95
111005	2	20	7/28	.010"	.015"	.138"	15
111010	3	20	7/28	.010"	.015"	.150"	17
111025	4	20	7/28	.010"	.015"	.164"	25
112005	2	18	7/26	.010"	.015"	.153"	19
112040	3	18	7/26	.010"	.015"	.168"	26
112105	4	18	7/26	.010"	.015"	.185"	35
112145	6	18	7/26	.010"	.015"	.235"	50
112160	8	18	7/26	.010"	.015"	.265"	68
112169	12	18	7/26	.010"	.015"	.302"	90
113002	2	16	19/29	.010"	.015"	.182"	27
113005	3	16	19/29	.010"	.015"	.196"	36
113007	4	16	19/29	.010"	.015"	.210"	48
113300‡	2	14	19/27	.012"	.015"	.218"	40
113301	2	14	19/27	.012"	.015"	.218"	40
113306	3	14	19/27	.012"	.015"	.231"	54
113307	4	14	19/27	.012"	.015"	.267"	70
113400‡	2	12	19/25	.012"	.015"	.254"	50
113402	2	12	19/25	.012"	.015"	.254"	50
113407	4	12	19/25	.012"	.015"	.305"	102

Most products available in boxes or reels with sequential footage markings and ripcords

‡ Color code chart 2, p. 42

Color code chart 1, p. 42