



### NON-PLENUM

General use indoors for:

- Solid or stranded bare copper
- Color coded PVC insulation
- 100% aluminum/polyester foil shield
- Tinned copper drain wire
- Grey PVC jacket
- NEC article 725 or 800
- UL listed CMR, 14 & 12 AWG CL2 or CL3
- Security systems
- Sound and audio
- Data, control and instrumentation



Most products available in boxes or reels with sequential footage markings and ripcords

CSC #	NO. OF COND.	AWG	STRAND	NOM INS	NOM. JKT THK	NOM. O.D.	NOM. CAP pf/ft	PKG WT LBS/1000'
161015	2	22	SOLID	.008"	.015"	.130"	44	13
161150	3	22	SOLID	.008"	.015"	.142"	44	19
161155	4	22	SOLID	.008"	.015"	.150"	44	24
161000*	2	22	7/30	.010"	.020"	.137"	45	15
161100	3	22	7/30	.010"	.020"	.148"	45	20
161200	4	22	7/30	.010"	.020"	.160"	45	23
161230	5	22	7/30	.010"	.020"	.176"	45	31
161240	6	22	7/30	.010"	.020"	.190"	45	32
161280	8	22	7/30	.010"	.025"	.210"	45	41
161325	12	22	7/30	.010"	.025"	.260"	45	59
161400	20	22	7/30	.010"	.025"	.318"	45	112
162000	2	20	7/28	.010"	.020"	.153"	50	24
162100	3	20	7/28	.010"	.020"	.165"	50	26
162152	4	20	7/28	.010"	.020"	.180"	50	30
162155	5	20	7/28	.010"	.020"	.200"	50	34
162160	6	20	7/28	.010"	.020"	.212"	50	38
163000**	2	18	7/26	.018"	.028"	.220"	24	28
163004	2	18	7/26	.010"	.020"	.168"	57	27
163100	3	18	7/26	.010"	.020"	.185"	57	33
163200	4	18	7/26	.010"	.020"	.201"	57	42
163204	5	18	7/26	.010"	.020"	.220"	57	51
163205	6	18	7/26	.010"	.020"	.250"	57	54
163218	8	18	7/26	.010"	.025"	.290"	57	83
163221	12	18	7/26	.010"	.025"	.327"	57	100
164000**	2	16	19/29	.032"	.032"	.310"	23	35
164004	2	16	19/29	.010"	.020"	.191"	67	34
164010	4	16	19/29	.010"	.020"	.239"	67	55
165000‡	2	14	19/27	.014"	.025"	.247"	63	57
165002	2	14	19/27	.014"	.025"	.247"	63	57
165005**	2	14	19/27	.032"	.032"	.340"	24	58
165010	4	14	19/27	.014"	.025"	.297"	63	60
165100‡	2	12	19/25	.014"	.025"	.290"	71	90
165102	2	12	19/25	.014"	.025"	.290"	71	90
165110	4	12	19/25	.014"	.025"	.335"	71	110

\* Available in different jacket colors

\*\* PE insulation, color code Black/Clear

Color code chart 1, p. 42

‡ Color code chart 2, p. 42