



NON-PLENUM

General use indoors for:

- Solid or stranded bare copper
- Color coded PVC insulation
- Each pair individually shielded with 100% aluminum/polyester foil shield
- Tinned copper drain wire for each individually shielded pair
- Grey PVC jacket
- NEC article 800
- UL listed CM or CMR
- Security systems
- Sound and audio
- Data, control and instrumentation



CSC #	NO. OF PAIRS	AWG	STRAND	NOM. INS THK	NOM. JKT THK	NOM. O.D.	NOM. CAP pf/ft	PKG WT LBS/1000'
171030	2	22	SOLID	.008"	.015"	.200"	44	27
171031	3	22	SOLID	.008"	.015"	.210"	44	45
171032	6	22	SOLID	.008"	.015"	.287"	44	82
171033	9	22	SOLID	.008"	.020"	.335"	44	105
171005*	2	22	7/30	.010"	.020"	.218"	45	28
171000+**	2	22	7/30	.008"	.020"	.208"	35	32
171145	2	22	7/30	.010"	.020"	.218"	45	32
171150	3	22	7/30	.010"	.020"	.234"	45	45
171200	4	22	7/30	.010"	.025"	.262"	45	54
171400	6	22	7/30	.010"	.025"	.315"	45	80
171557	9	22	7/30	.010"	.025"	.370"	45	105
171560	12	22	7/30	.010"	.025"	.418"	45	120
171570	19	22	7/30	.010"	.025"	.689"	45	220
171580	27	22	7/30	.010"	.025"	.760"	45	285
172000+	2	20	7/28	.010"	.020"	.220"	50	46
172065	3	20	7/28	.010"	.020"	.278"	50	60
172075	4	20	7/28	.010"	.020"	.318"	50	72
173292	2	18	7/26	.010"	.025"	.279"	57	56
173302	3	18	7/26	.010"	.025"	.297"	57	85
173310	4	18	7/26	.010"	.025"	.326"	57	115
173316	6	18	7/26	.010"	.025"	.393"	57	155

Most products available in boxes or reels with sequential footage markings and ripcords

* Plus auxiliary overall shield cabled on a common axis with a single common drain wire
 ** Polypropylene insulation cabled on a common axis with a common drain wire
 + Color code Black/Red - White/Green
 Color code chart 3, p. 42