



PLENUM



General use in air plenums without conduit for:

- Stranded bare copper
 - Color coded low smoke flame retardant polymer alloy insulation
 - 100% aluminum/polyester foil shield
 - Tinned copper drain wire for each individually shielded pair
 - Natural low smoke flame retardant polymer alloy jacket
 - NEC article 800
 - UL listed CMP
- Security systems
 - Sound and audio
 - Data, control and instrumentation

CSC #	NO. OF PAIRS	AWG	STRAND	NOM. INS THK	NOM. JKT THK	NOM. O.D.	NOM. CAP pf/ft	PKG WT LBS/1000'
111100*+	2	22	7/30	.010"	.015"	.212"	45	21
111192	2	22	7/30	.010"	.015"	.208"	45	21
111194*	2	22	7/30	.010"	.015"	.208"	45	21
111210	3	22	7/30	.010"	.015"	.224"	45	40
111302	4	22	7/30	.010"	.015"	.242"	45	45
111402	6	22	7/30	.010"	.015"	.295"	45	65
111413	9	22	7/30	.010"	.015"	.350"	45	78
111421	12	22	7/30	.010"	.015"	.398"	45	82
111027*	2	20	7/28	.010"	.015"	.210"	50	36
112102*	2	18	7/26	.010"	.015"	.259"	57	39
112195	2	18	7/26	.010"	.015"	.259"	57	39
112152*	3	18	7/26	.010"	.015"	.277"	57	50
112203	3	18	7/26	.010"	.015"	.277"	57	50
112210	4	18	7/26	.010"	.015"	.310"	57	76
112217	6	18	7/26	.010"	.015"	.373"	57	105

Most products available in boxes or reels with sequential footage markings and ripcords

* Color code Black/Red - White/Green - Brown/Blue
 + Plus auxiliary overall shield cabled on a common axis with a single common drain wire

Color code chart 3, p. 42