



NON-PLENUM

- Solid or stranded bare copper
- Color coded PVC insulation
- Grey PVC jacket
- NEC article 800
- UL listed CM or CMR

General use indoors for:

- Security systems
- Sound and audio
- Data, control and instrumentation

CSC #	NO. OF PAIRS	AWG	STRAND	NOM. INS THK	NOM. JKT THK	NOM. O.D.	PKG WT LBS/1000'
150100*	1	22	SOLID	.008"	.015"	.122"	11
150200*	1	22	7/30	.010"	.020"	.133"	10
180010	2	22	7/30	.010"	.020"	.207"	26
180020	3	22	7/30	.010"	.020"	.220"	34
180030	4	22	7/30	.010"	.020"	.241"	44
180040	6	22	7/30	.010"	.025"	.298"	62
180050	9	22	7/30	.010"	.025"	.327"	74
180060	12	22	7/30	.010"	.025"	.370"	95
150800	1	20	7/28	.010"	.020"	.148"	16
180110	2	20	7/28	.010"	.020"	.233"	28
180120	3	20	7/28	.010"	.025"	.254"	41
180130	4	20	7/28	.010"	.025"	.280"	51
151000*	1	18	7/26	.010"	.020"	.163"	23
173288	2	18	7/26	.010"	.020"	.260"	38
173298	3	18	7/26	.010"	.025"	.285"	53
173306	4	18	7/26	.010"	.025"	.314"	68

* Available in different jacket colors

Color code chart 3, p. 42
1 pr. color code chart 1, p. 42

Most products available
in boxes or reels
with sequential footage
markings and ripcords