



PLENUM

General use in air plenums without conduit for:

- Stranded bare copper
- 100% aluminum/polyester foil shield and tinned copper drain wire, as noted
- Color coded low smoke flame retardant polymer alloy insulation
- Natural low smoke flame retardant polymer alloy jacket
- NEC article 800
- UL listed CMP
- Security systems
- Sound and audio
- Data, control and instrumentation

UNSHIELDED



CSC #	NO. OF PAIRS	AWG	STRAND	NOM. INS THK	NOM. JKT THK	NOM. O.D.	PKG WT LBS/1000'
110105	1	22	7/30	.010"	.015"	.123"	13
111188	2	22	7/30	.010"	.015"	.197"	24
111005	1	20	7/28	.010"	.015"	.138"	15
111030	2	20	7/28	.010"	.015"	.223"	29
112005	1	18	7/26	.010"	.015"	.153"	19
112190	2	18	7/26	.010"	.015"	.250"	33
112197	3	18	7/26	.010"	.015"	.265"	50

Color code chart 3, p. 42

OVERALL SHIELDED



CSC #	NO. OF PAIRS	AWG	STRAND	NOM. INS THK	NOM. JKT THK	NOM. O.D.	NOM. CAP pf/ft	PKG WT LBS/1000'
110100	1	22	7/30	.010"	.015"	.128"	45	15
111190	2	22	7/30	.010"	.015"	.202"	45	25
111200	3	22	7/30	.010"	.015"	.215"	45	32
111300	4	22	7/30	.010"	.015"	.226"	45	38
111400	6	22	7/30	.010"	.015"	.283"	45	56
111000	1	20	7/28	.010"	.015"	.143"	50	19
111032	2	20	7/28	.010"	.015"	.228"	50	30
112000	1	18	7/26	.010"	.015"	.158"	57	27
112194	2	18	7/26	.010"	.015"	.255"	57	34
112200	3	18	7/26	.010"	.015"	.270"	57	53
112208	4	18	7/26	.010"	.015"	.308"	57	78
112215	6	18	7/26	.010"	.020"	.350"	57	90

Color code chart 3, p. 42

Most products available in boxes or reels with sequential footage markings and ripcords