



NON-PLENUM



Most products available in boxes or reels with sequential footage markings and ripcords

- Solid or stranded bare copper
  - Color coded PVC insulation
  - 100% aluminum/polyester foil shield
  - Tinned copper drain wire
  - Grey PVC jacket
  - NEC article 800
  - UL listed CM or CMR
- Security systems
  - Sound and audio
  - Data, control and instrumentation

General use indoors for:

CSC #	No. OF PAIRS	AWG	STRAND	NOM. INS THK	NOM. JKT THK	NOM. O.D.	NOM. CAP pf/ft	PKG WT LBS/1000'
161015	1	22	SOLID	.008"	.015"	.130"	44	13
171020	2	22	SOLID	.008"	.015"	.198"	44	21
171021	3	22	SOLID	.008"	.015"	.210"	44	32
171022	4	22	SOLID	.008"	.015"	.231"	44	41
171023	6	22	SOLID	.008"	.020"	.260"	44	59
171024	9	22	SOLID	.008"	.020"	.306"	44	80
171025	12	22	SOLID	.008"	.020"	.350"	44	94
161000*	1	22	7/30	.010"	.020"	.138"	45	15
171010	2	22	7/30	.010"	.020"	.212"	45	30
171100	3	22	7/30	.010"	.020"	.225"	45	32
171102	4	22	7/30	.010"	.025"	.246"	45	36
171104	6	22	7/30	.010"	.025"	.303"	45	47
171106	9	22	7/30	.010"	.025"	.332"	45	70
171108	12	22	7/30	.010"	.025"	.375"	45	94
162000	1	20	7/28	.010"	.020"	.153"	50	24
172050	2	20	7/28	.010"	.020"	.238"	50	33
172060	3	20	7/28	.010"	.025"	.259"	50	43
172070	4	20	7/28	.010"	.025"	.285"	50	64
163004	1	18	7/26	.010"	.020"	.168"	57	27
173290	2	18	7/26	.010"	.020"	.265"	57	46
173300	3	18	7/26	.010"	.025"	.290"	57	64
173308	4	18	7/26	.010"	.025"	.319"	57	87
173314	6	18	7/26	.010"	.025"	.370"	57	99

\* Available in different jacket colors

Color code chart 3, p. 42  
1 pr. color code chart 1, p. 42