



MINIATURE AUDIO, OVERALL SHIELDED



- Stranded tinned copper
- Color coded polypropylene insulation
- 100% aluminum/polyester foil shield
- 22 AWG tinned copper drain wire
- Pressure extruded Black PVC jacket
- NEC article 800
- UL listed CM

Specialized applications indoors for:

- Commercial systems
- Home theater
- Pro audio

CSC #	NO. OF COND	AWG	STRAND	NOM. INS THK	NOM. JKT THK	NOM. O.D.	NOM. CAP pf/ft	PKG WT LBS/1000'
161005	2	22	7/30	.008"	.020"	.150"	32	14

Color code chart 1, p. 42

HIGH STRAND OFC



- High strand OFC
- Color coded PVC insulation
- White PVC jacket
- NEC article 725
- UL listed CL3
- Available riser rated

Specialized applications indoors for:

- Commercial systems
- Home theater
- Pro audio

CSC #	NO. OF COND	AWG	STRAND	NOM. INS THK	NOM. JKT THK	NOM. O.D.	PKG WT LBS/1000'
151605	2	16	65/34	.010"	.025"	.265"	31
151630	4	16	65/34	.010"	.025"	.280"	51
151702	2	14	105/34	.014"	.025"	.280"	49
151712	4	14	105/34	.014"	.025"	.340"	91
151830	2	12	105/32	.020"	.040"	.325"	75
151834	4	12	105/32	.020"	.040"	.405"	137

Color code chart 1, p. 42

Most products available in boxes or reels with sequential footage markings and ripcords