



NON-PLENUM AND PLENUM

- Solid or stranded bare copper
- Color coded PVC insulation
- 100% aluminum/polyester foil shield
- Tinned copper drain wire
- Grey PVC jacket
- NEC article 725 or 800
- UL listed CMR

Specialized use indoors for:

- Security systems
- Sound and audio
- Intercom systems



Most products available in boxes or reels with sequential footage markings and ripcords

NON-PLENUM

CSC #	NO. OF COND/ CONSTRUCTION	AWG	STRAND	NOM. INS THK	NOM. JKT THK	NOM. O.D.	PKG WT LBS/1000'
161151	3 2/C-SHLD 1/C-UNSHLD	22	SOLID	.010"	.020"	.169"	18
161126	4 2/C-SHLD 2/C-UNSHLD	22	SOLID	.010"	.020"	.180"	23
171125*	6 1/PR-SHLD 2/PR-UNSHLD	22	SOLID	.010"	.025"	.230"	29
161125	3 2/C-SHLD 1/C-UNSHLD	22	7/30	.010"	.020"	.170"	18
161205	4 2/C-SHLD 2/C-UNSHLD	22	7/30	.010"	.020"	.175"	26
161337	17 2/C-SHLD 15/C-UNSHLD	22	7/30	.010"	.025"	.335"	105
162105	3 2/C-SHLD 1/C-UNSHLD	20	7/28	.010"	.020"	.200"	23
162150	4 2/C-SHLD 2/C-UNSHLD	20	7/28	.010"	.020"	.210"	34
163202	4 2/C-SHLD 2/C-UNSHLD	18	7/26	.010"	.020"	.240"	45

* Available in an outdoor version, PE jacket, CSC # 171128
Color code, consult CSC sales staff

- Solid or stranded bare copper
- Color coded polymer alloy PVC insulation
- 100% aluminum/polyester foil shield
- Tinned copper drain wire
- Plenum-rated jacket
- NEC article 800
- UL listed CMP

Specialized applications in air plenums without conduit for:

- Security systems
- Sound and audio
- Data, control and instrumentation

PLENUM

CSC #	NO. OF COND/ CONSTRUCTION	AWG	STRAND	NOM. INS THK	NOM. JKT THK	NOM. O.D.	PKG WT LBS/1000'
110124	3 2/C-SHLD 1/C-UNSHLD	22	SOLID	.007"	.015"	.131"	15
110125	3 2/C-SHLD 1/C-UNSHLD	22	7/30	.007"	.015"	.135"	16
111106	4 2/C-SHLD 2/C-UNSHLD	22	SOLID	.010"	.015"	.153"	18
111105	4 2/C-SHLD 2/C-UNSHLD	22	7/30	.010"	.015"	.155"	19
111304*	6 1/PR-SHLD 2/PR-UNSHLD	22	SOLID	.010"	.015"	.195"	38

Shielded – Black/Red, Unshielded – White/Green

* Color code, consult CSC sales staff