



COAXIAL

- UL listed CM
- Black PVC jacket

General use indoors for:

- CCTV
- Broadcast

CSC # DESCRIPTION	AWG STRAND TYPE	DIELECTRIC DIELEC O.D.	SHIELD MATERIAL	NOM. O.D.	NOM. ATTEN MHZ db/100	NOM IMP OHMS	NOM VEL OF PROP	NOM CAP pf/ft	
212070 MINI	25 SOLID BC	FPE .100"	95% BC BRAID	.135"	50	3.6	75	78%	
					100	5.3			17.5
212000 RG59/U	22 SOLID CCS	PE .144"	95% BC BRAID	.242"	50	2.4	73	66%	
					100	3.4			
					200	4.8			21.0
					400	7.1			
					900	10.9			
212060 RG59/U FLEX	22 7/30 BC	FPE .146"	95% BC BRAID	.242"	50	2.1	75	78%	
					100	3.0			
					200	4.5			17.3
					400	6.6			
					900	10.1			
212065* PREC VIDEO NON UL	20 SOLID BC	PE .198"	2-98% TC BRAIDS	.305"	1	.25	75	66%	
					10	.78			
					50	1.50			21.0
					100	2.70			
					400	5.30			
212053** RG59/U	20 SOLID BC	FPE .146"	95% BC BRAID	.242"	50	1.8	75	78%	
					100	2.5			
					200	3.4			17.0
					400	5.4			
					700	6.9			
211010 RG6/U	18 SOLID BC	FPE .182"	95% BC BRAID	.278"	10	.64	75	78%	
					50	1.5			
					100	2.1			17.3
					400	4.9			
					900	6.9			
211300 RG11/U	14 SOLID BC	FPE .285"	95% BC BRAID	.405"	50	1.0	75	78%	
					100	1.6			
					200	2.3			17.0
					400	3.8			
					700	4.7			



Most products available in boxes or reels with sequential footage markings

* Black polyethylene jacket

** Available in different jacket colors

CCTV UTP

- For use with CCTV over UTP

General use:

- CCTV

CSC #	AWG STRAND TYPE	PAIRS/ COND	DESCRIPTION	UL RATING
590315	24 Solid	2 Pair*	Category 5e (Video/PTZ/Power)	CL2R
	16 Stranded	2 Cond		
590319	24 Solid	2 Pair*	Category 5e (Video/PTZ/Power)	CL2P
	16 Stranded	2 Cond		
747841	24 Solid 16 Stranded	2 Pair* 2 Cond	Category 5e (Video/PTZ/Power)	Outdoor Rated

* Color Code Chart 5, p. 43

PVC & Plenum - 16 AWG cable white/red
Outdoor Rated - 16 AWG cable black/red

