



PLENUM

General use in air plenums without conduit for:

- UL listed CL2P and/or CMP
- Natural polymer alloy PVC jacket

- CCTV and Broadcast



CSC # DESCRIPTION	AWG STRAND TYPE	INSULATION	SHIELD MATERIAL	NOM. O.D.	NOM ATTEN MHZ db/100	NOM IMP OHMS	NOM VEL OF PROP	NOM CAP pf/ft
221170 MINI	25 SOLID BC	FFEP .078"	95% BC BRAID	.146"	1 .5	75	82%	17.0
					5 1.3			
					10 1.8			
					50 3.6			
					100 5.3			
					50 1.8			
					100 2.6			
					200 3.8			
221105 RG59/U	20 SOLID BC	FFEP .140"	95% BC BRAID	.202"	400 5.6	75	82%	16.5
					900 9.4			
					50 1.5			
					100 2.0			
220400 RG6/U	18 SOLID BC	FFEP .168"	95% BC BRAID	.238"	200 3.0	75	82%	17.0
					500 5.2			
					700 6.0			
					50 .9			
220500* RG11/U	14 SOLID BC	FFEP .280"	95% BC BRAID	.348"	100 1.4	75	82%	16.5
					200 2.2			
					400 3.6			
					700 4.6			

* Copolymer jacket

SIAMESE PLENUM

General use in air plenums without conduit for:

- UL listed CL2P or CMP
- Natural polymer alloy PVC jacket

- CCTV, DC Power & PTZ



CSC # DESCRIPTION	AWG STRAND TYPE	INSULATION	SHIELD MATERIAL	NOM. O.D.	NOM ATTEN MHZ db/100	NOM IMP OHMS	NOM VEL OF PROP	NOM CAP pf/ft
221125 RG59/U 1 Pair**	20 SOL BC	FFEP/.140" OD	95% BC BRAID	.202"X .355"	50 1.8	75	78%	16.5
					100 2.6			
592002 RG59/U 1 Pair**	20 SOL BC	FFEP/.140" OD	95% BC BRAID	.225"X .430"	50 1.8	75	78%	16.5
					100 2.6			
2 Pair†	18 BC 7/26	PVC/.010" THK	None					

Color code chart 2, p. 42

** Color Code - Black/Red

* Color code chart 1, p. 42

† Black/Red - White/Green

Most products available in boxes or reels with sequential footage markings