

SIAMESE



- UL listed CL2 or CM
- PVC jacket (212305 – BLK, 592000 – GRY)

General use indoors for:

- CCTV, DC Power & PTZ

CSC # DESCRIPTION	AWG STRAND TYPE	INSULATION	SHIELD MATERIAL	NOM. O.D.	NOM ATTEN MHZ db/100	NOM IMP OHMS	NOM VEL OF PROP	NOM CAP pf/ft
212305* RG59/U	20 SOL BC	FPE/.144" OD	95% BC BRAID	.242"X .460"	50 1.8 100 2.5	75	78%	17.0
1 Pair**	18 BC 7/26	PVC/.010" THK	None					
592000 RG59/U	20 SOL BC	FPE/.144" OD	95% BC BRAID	.320"X .450"	50 1.8 100 2.5	75	78%	17.0
1 Pair**	18 BC 7/26	PVC/.010" THK	None					
2 Pair†	22 BC 7/30	PVC/.010" THK	Each Pair Shielded					

* Available in different jacket colors

** Color Code - Black/Red

Color code chart 2, p. 42

† Black/Red - White/Green

SIAMESE OUTDOOR WITH MESSENGER

- Black polyethylene jacket
- Non UL

General use for:

- Outdoor CCTV

CSC # DESCRIPTION	AWG STRAND TYPE	INSULATION	SHIELD MATERIAL	NOM. O.D.	NOM ATTEN MHZ db/100	NOM IMP OHMS	NOM VEL OF PROP	NOM CAP pf/ft
211015 RG6/U	18 SOL BC	FPE/.180" OD	95% BC BRAID	.270"X .680"	10 .8 50 1.46	75	78%	17.0
1 Pair	16 BC 19/29	PVC/.010" OD	None					
14 AWG CCS Messenger								

OUTDOOR

- Includes moisture blocking agent



CSC # DESCRIPTION	AWG STRAND TYPE	INSULATION	SHIELD MATERIAL	NOM. O.D.	NOM ATTEN MHZ db/100	NOM IMP OHMS	NOM VEL OF PROP	NOM CAP pf/ft
211301 RG59/U	20 SOLID BC	FPE .146"	95% BC BRAID	.242"	50 1.8 100 2.5 200 3.4 400 5.4 700 6.9	75	78%	17.5
211011 RG6/U	18 SOLID BC	FPE .182"	95% BC BRAID	.278"	10 .64 50 1.5 100 2.1 400 4.9 900 6.9	75	78%	17.3
211198 RG11/U	14 SOLID BC	FPE .285"	95% BC BRAID	.405"	50 1.0 100 1.6 200 2.3 400 3.8 700 4.7	75	78%	17.0
791224 RG6/U	18 SOLID BC	FPE .182"	95% BC BRAID	.278"		75	78%	17.3
1 Pair	18 BC 7/26	PVC/.010 THK	None	.525"				
Overall Jacketed								

Most products available in boxes or reels with sequential footage markings