



### NON-PLENUM



- Solid bare copper
- Color coded PVC insulation
- Red PVC jacket
- NEC article 760
- UL listed FPLR

#### General use indoors for:

- Fire and security alarms
- Smoke detection systems

CSC #	NO. OF COND	AWG	STRAND	NOM. INS THK	NOM. JKT THK	NOM. O.D.	PKG WT LBS/1000'
250250	4	22	SOLID	.010"	.020"	.139"	20
250302	6	22	SOLID	.010"	.020"	.166"	24
250350	8	22	SOLID	.010"	.020"	.180"	36
250103*	2	18	SOLID	.010"	.020"	.151"	19
250110*	4	18	SOLID	.010"	.020"	.185"	31
250120	6	18	SOLID	.010"	.020"	.221"	47
250125	8	18	SOLID	.010"	.020"	.240"	63
250128	10	18	SOLID	.010"	.025"	.291"	76
250039*	2	16	SOLID	.010"	.020"	.182"	28
250045	4	16	SOLID	.010"	.020"	.211"	47
250017*	2	14	SOLID	.012"	.020"	.208"	45
250022	4	14	SOLID	.012"	.025"	.253"	73
250010	2	12	SOLID	.012"	.025"	.260"	65
250013	4	12	SOLID	.012"	.025"	.303"	106

Most products available in boxes or reels with sequential footage markings and ripcords

\* Available in different jacket colors

Color code chart 4, p. 42