



PLENUM

UNSHIELDED

General use in air plenums without conduit for:

- Solid bare copper
- Color coded polymer alloy PVC insulation
- Red polymer alloy PVC jacket
- NEC article 760
- UL listed FPLP
- Fire and security alarms
- Smoke detection systems

CSC #	NO. OF COND	AWG	STRAND	NOM. INS THK	NOM. JKT THK	NOM. O.D.	PKG WT LBS/1000'
121000*	2	18	SOLID	.009"	.015"	.140"	19
121050	4	18	SOLID	.010"	.015"	.175"	31
121063	6	18	SOLID	.010"	.015"	.211"	42
122005*	2	16	SOLID	.010"	.015"	.172"	27
122015	4	16	SOLID	.010"	.015"	.201"	46
123010*	2	14	SOLID	.012"	.015"	.198"	40
123016	4	14	SOLID	.012"	.015"	.233"	72
124010	2	12	SOLID	.012"	.015"	.240"	57
124020	4	12	SOLID	.012"	.018"	.283"	104

* Available in different jacket colors

Color code chart 4, p. 42



OVERALL SHIELDED

General use in air plenums without conduit for:

- Solid bare copper
- Color coded polymer alloy PVC insulation
- 100% aluminum/polyester foil shield
- Tinned copper drain wire
- Red polymer alloy PVC jacket
- NEC article 760
- UL listed FPLP
- Fire and security alarms
- Smoke detection systems

CSC #	NO. OF COND	AWG	STRAND	NOM. INS THK	NOM. JKT THK	NOM. O.D.	NOM. CAP pf/ft	PKG WT LBS/1000'
121005*	2	18	SOLID	.010"	.015"	.145"	58	22
121058	4	18	SOLID	.010"	.015"	.180"	58	32
121065	6	18	SOLID	.010"	.015"	.216"	58	44
122008*	2	16	SOLID	.010"	.015"	.177"	66	29
122020	4	16	SOLID	.010"	.015"	.206"	66	48
123015*	2	14	SOLID	.012"	.015"	.193"	67	47
123018	4	14	SOLID	.012"	.015"	.238"	67	74
124015	2	12	SOLID	.012"	.015"	.245"	76	65
124025	4	12	SOLID	.012"	.018"	.288"	76	107

* Available in different jacket colors

Color code chart 4, p. 42



Most products available in boxes or reels with sequential footage markings and ripcords