



UNSHIELDED & OVERALL SHIELDED

Designed to meet the survivability requirements of fire alarm cables in NFPA 72 as outlined in the National Fire Alarm Code and article 760 of the National Electric Code (NFPA 70).

General use indoors for:

- MICA glass tape
 - Color coded silicone rubber insulation
 - Red low-smoke zero halogen jacket
 - UL listed FPL/NPLF
 - Solid bare copper conductors
 - 300V rated
 - Flexible & easy to install
 - Available in reels only
- High-rise buildings, Hospitals, Tunnel, Subways, Airports, Hotels, Banks and more



| CSC # | No. OF COND | AWG | STRAND | SHIELDING | NOM. INS THK | NOM. JKT THK | NOM. O.D. | PKG WT LBS/1000' |
|--------|-------------|-----|--------|-------------|--------------|--------------|-----------|------------------|
| 700896 | 2 | 18 | SOLID | Copper Foil | .027" | .040" | .313" | 48 |
| 700897 | 2 | 16 | SOLID | Copper Foil | .027" | .040" | .329" | 68 |
| 700898 | 2 | 14 | SOLID | Copper Foil | .027" | .040" | .362" | 83 |
| 700899 | 2 | 12 | SOLID | Copper Foil | .027" | .040" | .398" | 115 |
| 704516 | 2 | 18 | SOLID | None | .027" | .040" | .331" | 44 |
| 704517 | 2 | 16 | SOLID | None | .027" | .040" | .347" | 56 |
| 704518 | 2 | 14 | SOLID | None | .027" | .040" | .382" | 72 |
| 704519 | 2 | 12 | SOLID | None | .027" | .040" | .417" | 98 |

For 2-hour burn fire rating the cable must be installed in 3/4" minimum EMT with steel set screw couplings