



NON-PLENUM AND PLENUM



- Solid bare copper
- Color coded polyethylene insulation
- 100% aluminum/polyester foil shield with tinned copper drain wire, as noted
- Red PVC jacket
- NEC article 760
- UL listed FPL

General use indoors for:

- Fire and security systems
- Smoke detection systems
- Microprocessor based systems

NON-PLENUM

CSC #	NO. OF PAIRS	AWG	SHIELD	NOM. INS THK	NOM. JKT THK	NOM. O.D.	NOM. CAP pf/ft	NOM. D.C.R. OHMS/1000	NOM. VEL OF PROP
250094	1	18	NONE	.016"	.027"	.198"	16	6.39	71%
250099	1	18	OVERALL	.016"	.027"	.202"	25	6.39	71%
250091	1	16	NONE	.016"	.027"	.224"	18	4.02	71%
250092	1	16	OVERALL	.016"	.027"	.220"	29	4.02	71%

Color code – Black/Red



- Solid bare copper
- Color coded Halar[®] insulation
- 100% aluminum/polyester foil shield with tinned copper drain wire, as noted
- Red polymer alloy PVC jacket
- NEC article 760
- UL listed FPLP

General use in air plenums without conduit for:

- Fire and security systems
- Smoke detection systems
- Microprocessor based systems

PLENUM

CSC #	NO. OF PAIRS	AWG	SHIELD	NOM. INS THK	NOM. JKT THK	NOM. O.D.	NOM. CAP pf/ft	NOM. D.C.R. OHMS/1000	NOM. VEL OF PROP
125000	1	18	NONE	.014"	.015"	.169"	16	6.39	71%
125005	1	18	OVERALL	.014"	.015"	.173"	30	6.39	71%
125020	1	16	NONE	.014"	.015"	.191"	18	4.02	71%
125025	1	16	OVERALL	.014"	.015"	.195"	31	4.02	71%

Color code – Black/Red

Most products available in boxes or reels with sequential footage markings and ripcords