



MULTI-CONDUCTOR, OVERALL SHIELDED



- Stranded bare copper
- Nylon covered color coded PVC insulation
- 100% aluminum/polyester foil shield
- Tinned copper drain wire
- Black PVC jacket
- NEC article 340
- UL listed TC
- 75°C wet, 90°C dry

Outdoor use for:

- Control systems
- Industrial signaling
- Direct burial
- Wet locations
- Sunlight resistant

CSC #	NO. OF COND	AWG	STRAND	NOM. INS THK	NOM. JKT THK	NOM. O.D.	PKG WT LBS/1000'
100500	2	18	7/26	.015" PVC .005" NYLON	.045"	.320"	55
100501	3	18	7/26	"	.045"	.335"	66
100502	4	18	7/26	"	.045"	.360"	77
100504	6	18	7/26	"	.045"	.420"	110
100506	8	18	7/26	"	.045"	.450"	130
100509	12	18	7/26	"	.045"	.510"	190
100575	2	16	7/24	"	.045"	.310"	64
100576	3	16	7/24	"	.045"	.335"	85
100577	4	16	7/24	"	.045"	.360"	105
100579	6	16	7/24	"	.045"	.450"	140
100580	7	16	7/24	"	.045"	.450"	160
100582	9	16	7/24	"	.045"	.480"	190
100584	12	16	7/24	"	.045"	.590"	250
100585	2	14	7/22	"	.045"	.335"	80
100587	4	14	7/22	"	.045"	.390"	120
100590	2	12	7/20	"	.045"	.375"	100
100592	4	12	7/20	"	.045"	.430"	150

14 AWG through 500 mcm sizes available, consult sales staff. All items available with a water block tape and/or Quad-rated - TC, PLTC, FPL, NPLF

Color code chart K2, p. 42