



**MULTI-PAIR OVERALL SHIELDED AND
MULTI-PAIR INDIVIDUALLY SHIELDED PLUS OVERALL SHIELDED**

- Stranded bare copper
- Nylon covered color coded PVC insulation
- 100% aluminum/polyester foil shield overall
- Tinned copper drain wire
- Tinned copper drain wire for each shielded pair
- Black PVC jacket
- NEC article 340
- UL listed TC
- 75°C wet, 90°C dry

Outdoor use for:

- Control systems
- Industrial signaling
- Direct burial
- Wet locations
- Sunlight resistant

OVERALL SHIELDED



CSC #	NO. OF PAIRS	AWG	STRAND	NOM. INS THK	NOM. JKT THK	NOM. O.D.	PKG WT LBS/1000'
OVERALL SHIELDED							
100602	2	18	7/26	.015" PVC .004" NYLON	.045"	.430"	95
100604	4	18	7/26	"	.045"	.480"	130
100606	6	18	7/26	"	.045"	.555"	180
100608	8	18	7/26	"	.060"	.630"	215
100610	10	18	7/26	"	.060"	.710"	300
100612	12	18	7/26	"	.060"	.750"	340
100622	2	16	7/24	"	.045"	.465"	110
100624	4	16	7/24	"	.060"	.525"	180
100626	6	16	7/24	"	.060"	.625"	240
100628	8	16	7/24	"	.060"	.725"	300
100630	10	16	7/24	"	.060"	.790"	365
100632	12	16	7/24	"	.080"	.870"	430
INDIVIDUALLY SHIELDED PLUS OVERALL SHIELDED							
100652	2	18	7/26	"	.050"	.440"	72
100654	4	18	7/26	"	.050"	.465"	90
100656	6	18	7/26	"	.060"	.505"	110
100658	8	18	7/26	"	.060"	.660"	221
100660	10	18	7/26	"	.060"	.790"	360
100662	12	18	7/26	"	.060"	.840"	410
100682	2	16	7/24	"	.050"	.470"	93
100684	4	16	7/24	"	.060"	.505"	117
100686	6	16	7/24	"	.060"	.575"	160
100688	8	16	7/24	"	.060"	.720"	300
100690	10	16	7/24	"	.080"	.910"	460
100692	12	16	7/24	"	.080"	.960"	530

**INDIVIDUALLY SHIELDED
PLUS OVERALL SHIELDED**



Color code - Black/White numbered pairs
Higher pair counts available, consult CSC sales staff.

All 600V tray cables are available with a water block tape