



**MULTI-PAIR OVERALL SHIELDED AND
MULTI-PAIR INDIVIDUALLY SHIELDED PLUS OVERALL SHIELD**

OVERALL SHIELDED



- Stranded bare copper
- PVC insulation
- 100% aluminum/polyester foil shield
- Tinned copper drain wire
- PVC jacket
- NEC article 340
- UL listed PLTC

Outdoor use for:

- Control systems
- Industrial signaling
- Direct burial
- Wet locations
- Sunlight resistant

CSC #	NO. OF PAIRS	AWG	STRAND	NOM. INS THK	NOM. JKT THK	NOM. O.D.	PKG WT LBS/1000'
100700*	1	20	7/28	.015"	.040"	.240"	30
100720	4	20	7/28	.015"	.040"	.355"	97
100730	8	20	7/28	.015"	.050"	.465"	158
100740	12	20	7/28	.015"	.050"	.545"	207
100750	16	20	7/28	.015"	.050"	.605"	278
100760	20	20	7/28	.015"	.060"	.650"	337
100770	24	20	7/28	.015"	.060"	.740"	401

* Available unshielded

Color code - Black/White numbered pairs

**INDIVIDUALLY SHIELDED
PAIRS PLUS
OVERALL SHIELD**



- Tinned copper drain wire for each individually shielded pair

CSC #	NO. OF PAIRS	AWG	STRAND	NOM. INS THK	NOM. JKT THK	NOM. O.D.	PKG WT LBS/1000'
100711	2	20	7/28	.015"	.055"	.375"	80
100721	4	20	7/28	.015"	.055"	.440"	115
100731	8	20	7/28	.015"	.055"	.560"	190
100741	12	20	7/28	.015"	.066"	.690"	268
100751	16	20	7/28	.015"	.066"	.770"	345
100761	20	20	7/28	.015"	.078"	.820"	412
100771	24	20	7/28	.015"	.078"	.950"	515

Color code - Black/White numbered pairs

All 300V tray cables are available with a water block tape